



## Female adaptor

- with stainless steel reinforcement ring (AISI430)
- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP
- gasket: NBR quality for drinkable water
- female thread: ISO 7 (parallel)
- colour: blue-black

| d    | Rp     | PN    | Code               | SP | GP  | Weight | D    | L    | l1   | l2   | l3   |
|------|--------|-------|--------------------|----|-----|--------|------|------|------|------|------|
| (mm) | (inch) | (bar) |                    |    |     | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) |
| 16   | ½      | 16    | <b>158 400 355</b> | 10 | 75  | 0.047  | 44   | 74   | 46   | 19   | 15   |
| 20   | ½      | 16    | <b>158 400 088</b> | 10 | 220 | 0.043  | 45   | 75   | 54   | 19   | 15   |
| 20   | ¾      | 16    | <b>158 400 089</b> | 10 | 200 | 0.048  | 45   | 77   | 54   | 19   | 16   |
| 25   | ½      | 16    | <b>158 400 090</b> | 10 | 170 | 0.061  | 53   | 81   | 59   | 21   | 15   |
| 25   | ¾      | 16    | <b>158 400 091</b> | 10 | 170 | 0.065  | 53   | 81   | 59   | 21   | 16   |
| 25   | 1      | 16    | <b>158 400 092</b> | 10 | 150 | 0.075  | 53   | 87   | 59   | 21   | 20   |
| 32   | ¾      | 16    | <b>158 400 093</b> | 10 | 110 | 0.097  | 64   | 90   | 66   | 23   | 16   |
| 32   | 1      | 16    | <b>158 400 094</b> | 10 | 110 | 0.105  | 64   | 94   | 66   | 23   | 20   |
| 32   | 1 ¼    | 16    | <b>158 400 095</b> | 10 | 100 | 0.118  | 64   | 97   | 66   | 23   | 22   |
| 40   | 1      | 16    | <b>158 400 096</b> | 90 | 0   | 0.155  | 75   | 105  | 76   | 26   | 20   |
| 40   | 1 ¼    | 16    | <b>158 400 097</b> | 90 | 0   | 0.163  | 75   | 107  | 76   | 26   | 22   |
| 40   | 1 ½    | 16    | <b>158 400 098</b> | 90 | 0   | 0.172  | 75   | 108  | 76   | 26   | 22   |
| 50   | 1      | 16    | <b>158 400 099</b> | 45 | 0   | 0.281  | 97   | 117  | 88   | 30   | 20   |
| 50   | 1 ¼    | 16    | <b>158 400 100</b> | 45 | 0   | 0.286  | 97   | 119  | 88   | 30   | 22   |
| 50   | 1 ½    | 16    | <b>158 400 101</b> | 45 | 0   | 0.298  | 97   | 119  | 88   | 30   | 22   |
| 50   | 2      | 16    | <b>158 400 102</b> | 40 | 0   | 0.327  | 97   | 125  | 88   | 30   | 26   |
| 63   | 1 ½    | 16    | <b>158 400 103</b> | 25 | 0   | 0.491  | 114  | 137  | 104  | 35   | 22   |
| 63   | 2      | 16    | <b>158 400 104</b> | 25 | 0   | 0.515  | 114  | 141  | 104  | 35   | 26   |
| 63   | 2 ½    | 16    | <b>158 400 105</b> | 18 | 0   | 0.564  | 114  | 148  | 104  | 35   | 31   |
| 75   | 2      | 16    | <b>158 400 106</b> | 18 | 0   | 0.824  | 135  | 173  | 133  | 41   | 26   |
| 75   | 2 ½    | 16    | <b>158 400 107</b> | 18 | 0   | 0.758  | 135  | 178  | 133  | 41   | 31   |
| 75   | 3      | 10    | <b>158 400 108</b> | 16 | 0   | 0.925  | 135  | 183  | 133  | 41   | 34   |
| 90   | 2      | 16    | <b>158 400 109</b> | 8  | 0   | 1.277  | 161  | 192  | 150  | 44   | 26   |
| 90   | 2 ½    | 16    | <b>158 400 110</b> | 8  | 0   | 1.320  | 161  | 197  | 150  | 44   | 31   |
| 90   | 3      | 10    | <b>158 400 111</b> | 8  | 0   | 1.357  | 161  | 199  | 150  | 44   | 34   |
| 110  | 3      | 10    | <b>158 400 112</b> | 6  | 0   | 1.940  | 185  | 226  | 175  | 53   | 34   |
| 110  | 4      | 10    | <b>158 400 113</b> | 6  | 0   | 2.046  | 185  | 232  | 175  | 53   | 40   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>