

**316**

CABLE JOINER

Use 3M Brand 316 to electrically connect two or three wire ends, insulate the connection and provide a moisture resistant seal. Recommended for use with low energy underground circuit wires, sprinkler systems, landscape lighting or other moisture resistant wires for applications of less than 30 volts.

FEATURES

- Self stripping
- Moisture resistant seal
- Can be crimped using slip joint pliers
- Used with insulated copper conductors

SPECIFICATIONS

- U-contact tin plated brass 0.5mm thick
- Insulator flame retardent nylon
- Black cap, white body
- Temperature 105°C
- Maximum voltage 30 VAC
- Sealant mineral oil base EG-3 Grease
- Voltage rating 30 VAC

WIRE RANGE

- 0.5mm² - 1.5mm² solid or stranded copper conductors with a maximum insulation 4mm
- Joins 2 or 3 unstripped conductors up to 1.5mm²



Note: UL Listed and CSA Certified for AWG only. Connector is not recommended for direct underground burial or other submerged applications.

WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

MODELS	CODE
3M 1.5mm ² Cable Joiners	316

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

CABLE_JOINER 316_V1.05-20

www.hrproducts.com.au

**PERTH**

PH: 08 9484 6500

FAX: 08 9455 1680

hrsales@hrproducts.com.au

SYDNEY

PH: 02 9616 1300

FAX: 02 9725 5283

infonsw@hrproducts.com.au

MELBOURNE

PH: 03 8458 7400

FAX: 03 9457 7400

infovic@hrproducts.com.au

BRISBANE

PH: 07 3080 6200

FAX: 07 3806 0533

infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8408 7200

FAX: 08 8341 0707

infosa@hrproducts.com.au