



32MM BRASS IMPACT SPRINKLER

Full Circle

Heavy Duty Brass full circle sprinkler with medium to high flow and is ideal for paddocks, feedlots, dust suppression and watering systems in mining and construction sites.

Features

- 32mm Male BSP thread
- Full Circle
- Triple nozzle
- Main and Secondary nozzle 28° Trajectory
- Tertiary nozzle 13° Trajectory
- Brass nozzles (sold separately)



VYR-155 - Triple Nozzle Performance Table

kPa	8.0mm x 6.3mm x 3.2mm		9.0mm x 6.3mm x 3.2mm		10.0mm x 6.3mm x 3.2mm		11.0mm x 6.3mm x 3.2mm		12.0mm x 6.3mm x 3.2mm		13.0mm x 6.3mm x 3.2mm		14.5mm x 6.3mm x 3.2mm	
	LPM	RAD (m)	LPM	RAD (m)	LPM	RAD (m)	LPM	RAD (m)	LPM	RAD (m)	LPM	RAD (m)	LPM	RAD (m)
400	141.7	25.5	160.0	26.0	183.3	26.5	200.0	28.0	220.0	28.5	250.0	29.5	283.3	31.5
500	158.3	26.5	180.0	27.0	205.0	27.5	223.3	29.0	248.3	30.0	283.3	31.0	318.3	32.5
600	173.3	27.0	195.0	27.5	225.0	29.0	245.0	30.5	275.0	31.0	313.3	32.0	346.7	33.5
700	186.7	28.0	213.3	28.5	243.3	30.0	266.7	31.5	300.0	32.0	338.3	33.0	371.7	34.5

Part No.	Description
VYR-155	32mm Brass Impact Sprinkler Full Circle - Triple Nozzle

* Performance table prepared under test conditions

* Nozzles sold separately

* Please specify nozzle when ordering